

M7250P PoE-PD Enabled 1000Base-TX to 1000Base-FX Media Converter

Product Features

- Provides direct media conversion for Gigabit copper & fiber
- Full wire speed performance
- SFP flexibility
- Best conversion latency
- Any packet size
- No packet length limitation
- Powered by PoE via Cat5, USB cable, or AC adapter
- Options for Bi-Directional communication
- Options for CWDM
- Optional DIN Rail mounting
- Link fault pass through
- Low power consumption



Technical Specifications

Standards:	IEEE 802.3ab, 802.3z, 802.3af PD (Powered Device)
Copper Port (TP):	Shielded RJ-45 jack Cat5e or higher UTP cable up to 100m Auto-negotiation for duplex and flow control
Fiber Port (FX):	Gigabit Ethernet 1000Base-FX SFP compliant Multi-Mode 50/125 or 62.5/125, Single-Mode 9/125 Fiber Far End Fault Indication support Auto-negotiation for flow control
LEDs:	Power Status, SFP On Status, Link Status, Optical Link Status
Power Input:	PoE: via Cat5 on RJ-45 from PSE device DC Jack: via external AC power adapter USB: via proprietary USB cable
PoE:	Input Voltage: 36-57 VDC via Cat5 Power Classification: Class 1
Environment:	Operating Temperature: -5° C ~ 55° C Storage Temperature: -20° C ~ 85° C Humidity: 5% ~ 95% non-condensing
Dimensions:	4.25 x 2.85 x 0.90 inches (108 x 72.5 x 23 mm)
Operating Voltage:	+7 - +57VDC Input Voltage
Mounting Support:	DIN Rail (Optional)
Approval:	FCC Class B, CE Class B, IEC60950-1

**M7250P PoE-PD Enabled
1000Base-TX to 1000Base-FX Media Converter**



USB-to-DC Cable



DRB-1 DIN Rail
Mounting Bracket

